


PRODUCTION

CONTROL WHERE IT COUNTS

2" Diameter Tower Lights



Tower Light Components

**24VAC/VDC
POLE MOUNT**

Model #	Description (Components Only)
LD-5221-100	LED, Red, 24VAC/DC, Cont., 3.5" Pole
LD-5221-110	LED, Red, 24VAC/DC, Cont., 10" Pole
LD-5221-120	LED, Red, 24VAC/DC, Cont., 24" Pole
LD-5221-130	LED, Red, 24VAC/DC, Cont., 36" Pole
LD-5222-100	LED, R/G, 24VAC/DC, Cont., 3.5" Pole
LD-5222-110	LED, R/G, 24VAC/DC, Cont., 10" Pole
LD-5222-120	LED, R/G, 24VAC/DC, Cont., 24" Pole
LD-5222-130	LED, R/G, 24VAC/DC, Cont., 36" Pole
LD-5223-100	LED, R/Y/G, 24VAC/DC, Cont., 3.5" Pole
LD-5223-110	LED, R/Y/G, 24VAC/DC, Cont., 10" Pole
LD-5223-120	LED, R/Y/G, 24VAC/DC, Cont., 24" Pole
LD-5223-130	LED, R/Y/G, 24VAC/DC, Con., 36" Pole
LD-5224-100	LED, R/Y/G/B, 24VAC/DC, Cont., 3.5" Pole
LD-5224-110	LED, R/Y/G/B, 24VAC/DC, Cont., 10" Pole
LD-5224-120	LED, R/Y/G/B, 24VAC/DC, Cont., 24" Pole
LD-5224-130	LED, R/Y/G/B, 24VAC/DC, Cont., 36" Pole
LD-5225-100	LED, R/Y/G/B/W, 24VAC/DC, Cont., 3.5" Pole
LD-5225-110	LED, R/Y/G/B/W, 24VAC/DC, Cont., 10" Pole
LD-5225-120	LED, R/Y/G/B/W, 24VAC/DC, Cont., 24" Pole
LD-5225-130	LED, R/Y/G/B/W, 24VAC/DC, Cont., 36" Pole
LD-5221-101	LED, Red, 24VAC/DC, Flashing, 3.5" Pole
LD-5221-111	LED, Red, 24VAC/DC, Flashing, 10" Pole
LD-5221-121	LED, Red, 24VAC/DC, Flashing, 24" Pole
LD-5221-131	LED, Red, 24VAC/DC, Flashing, 36" Pole
LD-5222-101	LED, R/G, 24VAC/DC, Flashing, 3.5" Pole
LD-5222-111	LED, R/G, 24VAC/DC, Flashing, 10" Pole
LD-5222-121	LED, R/G, 24VAC/DC, Flashing, 24" Pole
LD-5222-131	LED, R/G, 24VAC/DC, Flashing, 36" Pole
LD-5223-101	LED, R/Y/G, 24VAC/DC, Flashing, 3.5" Pole
LD-5223-111	LED, R/Y/G, 24VAC/DC, Flashing, 10" Pole
LD-5223-121	LED, R/Y/G, 24VAC/DC, Flashing, 24" Pole
LD-5223-131	LED, R/Y/G, 24VAC/DC, Flashing, 36" Pole
LD-5224-101	LED, R/Y/G/B, 24VAC/DC, Flashing, 3.5" Pole
LD-5224-111	LED, R/Y/G/B, 24VAC/DC, Flashing, 10" Pole
LD-5224-121	LED, R/Y/G/B, 24VAC/DC, Flashing, 24" Pole
LD-5224-131	LED, R/Y/G/B, 24VAC/DC, Flashing, 36" Pole
LD-5225-101	LED, R/Y/G/B/W, 24VAC/DC, Flashing, 3.5" Pole
LD-5225-111	LED, R/Y/G/B/W, 24VAC/DC, Flashing, 10" Pole
LD-5225-121	LED, R/Y/G/B/W, 24VAC/DC, Flashing, 24" Pole
LD-5225-131	LED, R/Y/G/B/W, 24VAC/DC, Flashing, 36" Pole
LD-52xx-BASE	OPTIONAL BASE for base mount

- Red, Yellow, Green, Blue or Clear
- Easy Install
- 2" Diameter Light
- LED
- Continuous
- Easy Change LED Bulbs

LED lights are light stack components and come with choice of pole length. Each tower provides a pole mounting bracket. Optional base mount available as adder option.

Standard Stack Light specs and features:
LED lighting using LED replaceable bulbs.

Lens are fixed colors and can not be re-arranged. Color order is from top to bottom:

- 2 Color: R/G
- 3 Color: R/Y/G
- 4 Color: R/Y/G/B
- 5 Color: R/Y/G/B/W

Continuous tower component is rated IP65.
Flashing tower component is rated IP55.
Standard light size is 2 inch diameter.
Bulbs are 24VAC/VDC_5W LED per color.